

Our multi-purpose model: X1FA 1000/1500

Folding tail-lift with a capacity of 1.000 kg or 1.500 kg



Light and multi-purpose: The tail-lift solution for occasional use on delivery trucks.



Guaranteed unproblematic loading and unloading on ramps or with forklift trucks.

Your advantages unfold with this Sörensen lift:

- + Fast assembly through bolted assembly plates
- + No welding operations are necessary
- Low own weight of the lift while maintaining its high stability improves the payload of the truck
- + Classic loading and unloading of the vehicle is possible without using the tail lift
- + Lower fuel consumption and reduced CO₂ emissions.
- Rear bumper according to the directive 2006/20/EG for an unlimited vehicle weight
- Low life cycle costs through compact design and maintenance-free bushings
- The nitrate surface treatment of the cylinders, offers protection against corrosion

Sörensen Hydraulik GmbH • Osterrade 3 • 21031 Hamburg • +49 (0)40/ 739 606 0 • www.soerensen.de

Plus-point product diversity

Folding tail-lift with a capacity of 1.000 kg or 1.500 kg for the distribution sector.



Product information

🕂 Lifting mechanism

Black KTL coated (RAL 9005), maintenance-free bushings, pre-drilled assembly plates to bolt the lift onto the vehicle frame, crash bar in one piece (tested by TÜV and EU-approved), electrical interface according to VEHH norms

+ Lifting capacity / load distance

1.000 kg / 1.500 kg at 600 mm

+ Loading height

Min. 1.100 mm (loaded), max 1.350 mm with an arm lenght of 875 mm

🕂 Platform

Aluminum

Standard equipment

- Waterproof control box
- Bolted plates for fast assembly
- 🕂 2 button hand-held control with wanderlead
- Installation ready steel mainframe, black coated, with brackets
- + Automatic ground tilting
- + Static over roll plate
- + Controls for servicing the lift (Service Switch)
- + Quiet running power pack with thermo switch
- Maintenance-free bushinas
- + Warning flags
- 🕂 The platform can be tilted at any loading position

Accessories (in extracts)

- + Warranty extension from 24 to 36 months
- Flat 2 button safety foot controls on the platform
- Warning flashlights on platform corners
- 🕂 2 button hand-held control with wanderlead
- Case for rear lights
- 🕂 Hydraulic leveling
- Cart stops
- 🕂 Rear beam
- Mass cable
- + Cross milling on the platform
- + Towing ball coupling (to be bolted)





Option: Towing ball coupling, quick and easy installation, retro fittable.

TYPE:	X1FA 1000	
	mm	kg
Platform height / weight:	1.400	395
TYPE:	X1FA 1500	
	mm	kg
Platform height / weight:	1.400	410
Rear beam:		20
Case for rear lights:		15



The patented X1 Technology makes it possible:

- Unrivaled light tail lifts, maximum stability for optimal loading capacity
 - and efficient workflows. Compact design, fewer construction
 - parts exclusively high quality and maintenace-free bushings for minimum life cycle costs of the tail lift.