

Plus-point product diversity

Retractable tail lift with a capacity of 1.000 kg or 1.500 kg, low in height and needing very little assembly depth.



Our multi-purpose model : UASX 1008/1508

Retractable tail lift with a capacity of 1.000 kg or 1.500 kg



Multi-purpose loading system for vehicles with fixed or interchangeable bodies, as well as those fitted with a tow-ball unit.



Guaranteed unproblematic loading and unloading on ramps or with forklift trucks (a version for interchangeable bodies is also available)

The versatile partner with intelligent advantages:

- + Fast assembly through four bolted assembly plates, no welding is necessary on the vehicle.
- + Loading and unloading on ramps or with forklift trucks is not a problem
- + Its reduced height of 280 mm and assembly depth of 1.200 mm allows an assembly on 7,5 t trucks
- + Spring assisted folding and unfolding of the platform
- + Even more versatile thanks to its interchangeable system
- + Rear bumper according to the directive 2006/20/EG for an unlimited vehicle weight
- + Anodized aluminum platform
- + Static bridge plate, eliminating the need for an additional plate

Plus-point product diversity

Retractable tail lift with a capacity of 1.000 kg or 1.500 kg low in height and needing very little assembly depth.

Sörensen

The tail lift experts

Product information

+ Lifting mechanism

Black KTL coated (RAL 9005), maintenance-free bushings, pre-drilled assembly plates to bolt the lift onto the vehicle frame, crash bar in one piece (tested by TÜV and EU-approved), electrical interface according to VEHH norms

+ Lifting capacity / load distance

1.000 kg / 1.500 kg at 600 mm

+ Lifting arm lengths / loading height

Lifting arm length 1.100 mm max. / loading height max. 1.620 mm

+ Platform

Aluminum, anodized

Standard equipment

- + Waterproof control box
- + Bolted plates, for fast assembly
- + 2 button hand-held control with wanderlead
- + Installation ready steel mainframe, black coated, with brackets
- + Automatic ground tilting
- + Static over roll plate
- + Controls for servicing the lift (Service Switch)
- + Quiet running power pack with thermo switch
- + Maintenance-free bushings
- + Warning flags
- + The platform can be tilted at any loading position

Accessories (in extracts)

- + Warranty extension from 24 to 36 months
- + 3 button hand-held control with wanderlead
- + Flat 2 button safety foot controls on the platform
- + Warning flashlights on platform corners
- + Case for rear lights
- + Hydraulic leveling
- + Different types of cart stop
- + Rear beam
- + Mass cable
- + Cross milling on the platform
- + Towing ball coupling (to be bolted)



TYPE:	UASX	
	mm	kg
Platform height / weight:	1.500	524
	1.700	537

...lifts for life